



PFN-7244VM-AT

- * 24-Port 10/100/1000BaseT(X) PoE with 4 Combo SFP Open Slots
- * IEEE 802.3at, up to 30W per port
- * Maximum 460W PoE power budget
- * 19" Rack-Mount Metal Case
- * Offers Web-based Configuration and Management
- * Powerful L2 features
- * Up to 9.6K Jumbo Frame

24-port Gigabit PoE with 4 Combo SFP Rack-mount Web Smart Switch

Introduction

PFN-7244VM-AT is a 24-port 10/100/1000MPoE with 4 Combo SFP Rack-mount Web Smart Switch. The switch supports IEEE 802.3at Power over Ethernet standard, maximum 460W power consumption per system. The switch also provides exceptionally smart Web management features, such as VLAN, QoS, RSTP, IGMP Snooping, LACP, IEEE 802.1X, Storm Control...etc. The switch is standard 19" rack-mount design to fit into the rack environment. With these features, the switch is a superb choice for medium or large network environment to strengthen its network connection and efficiency.

IEEE 802.3at Power over Ethernet (PoE) ports

PFN-7244VM-AT features 24 IEEE 802.3at Power over Ethernet (PoE) ports supplying up to 30 watts per port. This product can convert standard 100~240V/AC power into low-voltage DC that runs over existing LAN cable to power up IEEE 802.3at compliant network accessories. It also features PoE awareness to verify whether the network device receives power is IEEE 802.3at compliant, or only the data will be sent through LAN cable. By adding PFN-7244VM-AT to existing networking, installing networking products such as Access Points and IP cameras can be easily managed and set up. Wireless device deployments are easily located with available power outlets and network administrators don't need to use heavy AC power adapters anymore.

4 Combo SFP Open Slots

PFN-7244VM-AT supports 4 Combo SFP open slots to uplink to servers, storage, or other switching devices for long loop reach applications.

High-Speed Networking and Jumbo Frames Support

PFN-7244VM-AT provides an excellent solution for expanding your Gigabit network. By Gigabit speed, this product provides high flexibility and high bandwidth connectivity to servers, workstations and other attached devices. It enables you to save time transferring large files. In addition, it also supports Jumbo Frames 9.6K to improve network utilization of large file transfers.

Exceptionally Smart

The PFN-7244VM-AT features a management interface that can be managed through a Web Browser and it provides Smart features that are ideal for network applications and basic monitoring tools to improve network efficiency. Through a Web-based interface, an administrator can set up VLANs to segregate traffic, QoS to prioritize mission-critical data, RSTP to avoid network loop, link aggregation to create fat traffic pipelines, bandwidth control to limit traffic load and IEEE 802.1X to secure port access on your network. All of these features offer extra protection on the network edge.

Advanced Security

PFN-7244VM-AT supports specific IP Addresses filtering for every port, and then only identifiers have the privilege to pass through the specific ports. On port access control, the switch also supports IEEE 802.1x port authentication.

Technical Specifications

Standards	Ethernet: IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.ab 1000BaseT, IEEE 802.3z 1000BaseSX/LX IEEE 802.3x Full-duplex and Flow Control IEEE 802.1Q VLAN IEEE 802.3ad Link Aggregation Control Protocol IEEE 802.1D Spanning Tree Protocol IEEE 802.1w Rapid Spanning Tree Protocol IEEE 802.1p Class of Service IEEE 802.1X Port-based Network Access Control IEEE 802.3at Power Over Ethernet (PoE)
Performance	10/100/1000M RJ-45 Ports: 24 ports with IEEE 802.3at PoE Gigabit SFP: 4, Combo with 4 10/100/1000M RJ-45 MAC Address: 8K Numbers of VLAN ID: 4K Buffer Memory: 500 Kb Jumbo Frames: 9.6 K Transmission Method: Store and Forward
Smart Features	Rapid Spanning Tree Protocol IGMP Snooping V1&V2 LACP/Trunk: up to 8 groups Quality of Service: up to 4 queues, 802.1p PoE Control: PoE Port Enabled/Disable, Status IEEE 802.1X, Source IP Filter Storm Control: Broadcast, Multicast, Flood Unicast Port: Port State, Speed/Duplex, Flow Control Rate Limiting, Port Mirroring Management: Web GUI, SNMP, Password protection Configuration upload/download, Firmware upgrade
Filtering/Forwarding Rates	10Mbps port - 14,880pps 100Mbps port - 148,800pps 1000Mbps port -1,488,000pps
Transmission Media	10BaseT Cat. 3, 4, 5 UTP/STP, 100BaseTX Cat. 5 UTP/STP 1000BaseT Cat. 5E UTP/STP
Led Indicators	Per Port: Link/Act; PoE On/Off Per Unit: Power
Power Input	100~240V/AC, 50~60Hz
Power Output	56V /DC Per Port Output (Max. 250W/ 500W)
PoE budget	210W/ 460W
Dimensions	44 x 440 x 331 mm (H x W x D)
Weight	4.1Kg/ 4.6Kg
Operating Temperature	0 to 45°C
Storage Temperature	-20 to 85°C
Humidity	10 to 90% RH (non-condensing)
Certifications	FCC Class A, CE mark, Commercial